



× × 110mm×45mm×50mm

1

DT-7141H

2

- ❖ HDMI
- ❖ DR-2108A 1080P 300MHz-860MHz
- ❖ 1-3 280-320MS
- ❖ 12W
- ❖ 224g
- ❖ H.264
- ❖
- ❖
- ❖ USB
- ❖ DC12V/DC24V DC 10V-26V
- ❖
- ❖
- ❖ 230KM/H

3

		300~2400MHz, 10 KHz
		300MHz-860MHz≤1W 860MHz-2400MHz≤500mW
		COFDM DVB-T
		2M 4M,6M,7M,8M
		1-8Mbps
		1/2,2/3,3/4,5/6,7/8
		1/32,1/16,1/8,1/4
时		QPSK,16QAM,64QAM
		2K 8K
		≤25dB
		1920×1080_60P,1920×1080_50P 1920×1080_60i,1920×1080_50i 1280×720_60P,1280×720_50P 720×576_50i,720×480_60i
		MPEG-4 AVC/H.264
		0.8Mbps~30Mbps
		CBR
		IPPP
		MPEG-1 Layer2
		48KHz
		24-bit
		64Kbps-192Kbps
		280-320MS
		RPSMA MMCX 50Ω
		HDMI
		RF RPSMA
		DC 24V/DC 12V
		-10 ~50 () -20 ~75 ()
		PAL/NTSC
		300MHz-860MHz, 1-3
		≤224

110mm×45mm×50mm

	100MHz-932MHz	
	COFDM DVB-T	
	75Ω	
	HDMI CVBS	
	-95.8dBm	
	6M/7M/8M	
时	QPSK, 16QAM, 64QAM	
	1/32, 1/16, 1/8, 1/4	
	1/2, 2/3, 3/4, 5/6, 7/8	
	2K 4K 8K	
	MPEG-4 AVC /H.264 HP@L4 MPEG-2 MP @HL/ML	
	4:3/16:9	
	PAL/NTSC	
	1±0.3Vpp	
	HDMI	1920 1080_30P,1920 1080_25P 1920 1080_60i,1920 1080_50i 1280 720_60P,1280 720_50P 720 576_50i,720 480_60i
	CVBS	720 576_50i 720 480_60i
	MPEG-2/HE_AAC(DD/DD+)	
	及 +	
	1 RCA	2 RCA 及
	USB	
	≤10W	
	DC+12V~24V±10%	
	-10 ~+50	
	214g	
	172mm 82mm 36mm	